

EP-6KMG

HYBRID SOLAR INVERTER / SINGLE PHASE

HYBIRD ECOPOWER 6KW 1 PHA

MODEL: EP-6KMG



- Parallel Operation
Up to 6 Units
- High Efficiency
Max. 98%
- Touchscreen
- 2 Independent AC Inputs
2 Outputs
- Current
Transformer
- Wide MPPT
Range 50-450V
- Maximize PV Input
Power(2 MPPTs)

MODEL	EP-3KMG	EP-6KMG
Phase	1-phase in /1-phase out	
Maximum Pv Input Power	4500W	9000W
Rated Output Power	3000W	6000W
Maximum Charging Power	3000W	6000W
GRID-TIED OPERATION		
PV INPUT (DC)		
Maximum DC Voltage	/	500Vdc
Start-up Voltage /Initial Feeding Voltage	/	90Vdc/120Vdc
MPPT Voltage Range	/	60Vdc-450Vdc
Number of MPPT Trackers /Maximum Input Current	/	2/18A
GRID OUTPUT (AC)		
Nominal Output Voltage	/	220/230/240VAC
Output Voltage Range	/	184-264.5 VAC or 195.5-253 VAC or 184-264.4 VAC(Selectable)
Nominal Output Current	/	26.1A
Power Factor	/	>0.99
EFFICIENCY		
Maximum Conversion Efficiency (DC/AC)	/	97%
OFF-GRID OPERATION		
AC INPUT		
AC Start-up Voltage /Auto Restart Voltage	120-140 VAC/180 VAC	
Acceptable Input Voltage Range	90-280 VAC	
Frequency Range	50 Hz/60 Hz(Auto sensing)	
Maximum AC Input Current	18A	40A
PV INPUT (DC)		
Maximum DC Voltage	500Vdc	520Vdc
MPPT Voltage Range	50Vdc-450Vdc	
Number of MPPT Trackers/Maximum Input Current	1/18A	2/18A
GRID OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Output Voltage Range	184-264.5 VAC or 195.5-253 VAC or 184-264.4 VAC(Selectable)	
Nominal Output Current	13A	26.1A
AC INPUT		
AC Start-up Voltage/Auto Restart Voltage	120-140 VAC/180 VAC	
Acceptable Input Voltage Range	90-280VAC or 170-280 VAC	
Maximum AC Input Current	16A	40A
BATTERY MODE OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Efficiency (DC to AC)	93%	
BATTERY & CHARGER		
Nominal DC Voltage	24Vdc	48Vdc
Maximum Solar Charging Current	100A	135A
Maximum AC Charging Current	100A	135A
Maximum Charging Current	100A	135A
GENERAL		
PHYSICAL		
Dimension, D x W x H(mm)	451x353x160.2	471x444x200
Net Weight (kg)	12.3	18.5
INTERFACE		
Parallel Function	/	Yes, 6 units
Communication Port	RS232/RS485/Wi-Fi	RS232/RS485/CAN/Wi-Fi/Dry contact
ENVIRONMENT		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
IP degree	IP65	
Operating Temperature	-10℃ ~ 50℃	
Storage Temperature	-15℃ ~ 60℃	